
SatNOGS Config

Release 0.6.3+0.g9b64c8d.dirty

SatNOGS

Dec 29, 2020

CONTENTS

1	Table of Contents	3
1.1	User guide	3
1.1.1	Requirements	3
1.1.2	Installation	3
1.1.3	Usage	3
1.1.3.1	Basic	3
1.1.3.2	Advanced	3
1.1.3.3	Show	4
1.1.3.4	Upgrade	4
1.1.3.5	Update	4
1.1.3.6	Reset	4
1.1.3.7	Apply	4
1.2	Developer guide	4
1.2.1	Installation	4
1.2.2	Configuration	4
1.2.3	Extending	4
1.2.4	Modifying the menu	5
1.2.5	Code Quality Assurance	5
1.2.6	Automation	5
1.3	Modules reference	5
1.3.1	satnogsconfig	5
1.3.2	satnogsconfig.config	5
1.3.3	satnogsconfig.helpers	6
1.3.4	satnogsconfig.menu	6
2	Indices and tables	7
	Python Module Index	9
	Index	11

SatNOGS Config is a utility for generating the configuration for a Debian-based SatNOGS client system. It is a menu driven configuration tool built on-top of `pythondialog`. The main purpose of this utility is to create the YAML configuration file for SatNOGS Client Ansible which provisions the system. In addition to that, it interacts with `satnogs-setup`, which is a wrapper to bootstrap Ansible, upgrades the system packages using APT and probes the hardware to show the user a more limited set of configuration options.

TABLE OF CONTENTS

1.1 User guide

1.1.1 Requirements

- Python 3.4+

1.1.2 Installation

To install SatNOGS Config run:

```
$ pip install satnogs-config
```

This will install a console script called `satnogs-config`.

1.1.3 Usage

To execute the script, run it on the command line:

```
$ satnogs-config
```

The main menu will be shown

1.1.3.1 Basic

The `Basic` sub-menu contains the minimum required configuration options for provisioning the SatNOGS client system.

1.1.3.2 Advanced

The `Advanced` sub-menu contains a larger set of configuration options. It is intended for advanced users and contains options categorized by component.

1.1.3.3 Show

The `Show` option displays the current configuration file.

1.1.3.4 Upgrade

The `Upgrade` option calls APT utilities to upgrade the distribution packages.

1.1.3.5 Update

The `Update` option works in conjunction with `satnogs-setup` to re-bootstrap Ansible and update the configuration tools.

1.1.3.6 Reset

The `Reset` option resets the configuration file generated by the utility, effectively removing all the configuration options set by the user.

1.1.3.7 Apply

The `Apply` button runs SatNOGS Client Ansible which provisions Debian to become a SatNOGS client system.

1.2 Developer guide

1.2.1 Installation

To install SatNOGS Config for development run in the project root directory:

```
$ pip install -e .
```

1.2.2 Configuration

This project uses `python-dotenv`. Configuration of `satnogsconfig/settings.py` can be overridden by setting the respective environment variables or an `.env` file placed on the project root directory.

1.2.3 Extending

SatNOGS Config functionality can be extended by implementing additional helpers. The helpers are used to enhance menu functionality beyond the core function of generating a YAML file for Ansible.

1.2.4 Modifying the menu

The menu itself is also expressed in YAML format. The menu structure is defined in `menu.yml` file and shipped along with the package.

1.2.5 Code Quality Assurance

The following code quality assurance tools are used in this project:

- flake8
- isort
- yapf
- pylint

1.2.6 Automation

tox is used to automate development tasks. To execute the default list of tasks run:

```
$ tox
```

1.3 Modules reference

1.3.1 satnogsconfig

1.3.2 satnogsconfig.config

Configuration module

class `satnogsconfig.config.Config(filename)`
Manage configuration file

Parameters `filename` (*str*) – File path of configuration

`_load_config()`

Load and parse YAML configuration

Returns Configuration dictionary

Return type dict or NoneType

`clear_config()`

Clear configuration file

`dump_config(to_file=False)`

Dump configuration in YAML format

Parameters `to_file` (*bool, optional*) – Dump to file

Returns YAML configuration

Return type str

`get_variable(variable)`

Get variable value from configuration

Parameters **variable** (*str*) – Variable to get the value

Returns Value of variable

Return type str or bool or NoneType

set_variable (*variable, value*)

Set variable value in configuration

Parameters

- **variable** (*str*) – Variable to set the value
- **value** (*str or bool or NoneType*) – Value of variable

1.3.3 satnogsconfig.helpers

1.3.4 satnogsconfig.menu

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

S

`satnogsconfig.config`, [5](#)

Symbols

`_load_config()` (*satnogsconfig.config.Config*
method), 5

C

`clear_config()` (*satnogsconfig.config.Config*
method), 5

`Config` (*class in satnogsconfig.config*), 5

D

`dump_config()` (*satnogsconfig.config.Config*
method), 5

G

`get_variable()` (*satnogsconfig.config.Config*
method), 5

S

`satnogsconfig.config` (*module*), 5

`set_variable()` (*satnogsconfig.config.Config*
method), 6